#### Chapter 18A

# Foundations and Retaining Walls Comparison Summary

The foundation design chapters, Chapter 18 (Soils and Foundations) in the *IBC* and Chapter 36 (Soils, Foundations, and Retaining Walls) of *NFPA 5000*, cover the design of foundations and earth-retaining structures.

#### IBC 2003

Chapter 18 of the *IBC* is 25 pages long. The chapter has been organized differently compared to the *CBC*, and includes greatly expanded coverage of foundation design. A useful feature of *CBC* Chapter 18 is the extensive cross-referencing provided, which directs the user to appropriate provisions in other chapters of the code. Seismic Design Category triggers many foundation design requirements. These triggers will require evaluation by OSHPD.

Coverage of deep foundation systems is much more extensive than in the *CBC*. The useful table of minimum foundation depth and thickness under light frame walls is retained. *IBC* provisions for unreinforced concrete and masonry basement walls will not be adopted for OSHPD's jurisdiction, and should be repealed for all other occupancies in California.

#### NFPA 5000

In *NFPA 5000*, soils, foundations, and retaining walls are covered in the 10 pages of Chapter 36. Chapter 36 contains provisions for a number of different types of foundation systems. A number of the provisions in Chapter 36 are vague. For example, Section 36.2.3.3 uses the phrase "safe side slopes, as determined by the AHJ", which seems to force the responsibility for determination of safe side slopes on to the building official. In Table 36.3.4(a), which gives permissible soil bearing values, the terms "soft", "medium", "hard", "compact", "loose" may be problematic for interpretation and use by typical users (non-geotechnical engineer) of these tables. In addition, there are no permissible bearing values for gravel and rock sites.

Many of the References in the Chapter 36 appear overbroad. For example, Section 36.1.1 states that foundations must meet ASCE7-02, Sections 9 and A9.7, over 100 pages of material (the entire Seismic Design Section). Section 36.9.1, retaining walls, stated that they shall be designed to resist design loads in Chapter 35, and to insure stability against overturning, sliding, excessive foundation pressure, and water uplift. Again reference is made to the entire Chapter. Further, the requirements are vague. What constitutes "excessive foundation pressure?" More precise language is needed. Another example is steel piles, covered in Section 36.5.7. Basically, this section requires that steel piles meet the requirements of Chapter 44, the steel chapter. Unfortunately, we could not locate any piling requirements in Chapter 44. Therefore,

the user would have to begin searching the referenced publications for the appropriate provision. In contrast, users of the *IBC* need only refer to Section 1809.3, which provides specific materials, allowable stress, and dimension information.

#### Summary

*IBC* Chapter 18 covers soils and foundations in a more comprehensive, precise, and enforceable manner than *NFPA 5000* Chapter 40. The overly broad references are especially troubling, as they force both the designer and building official to search through large volumes materials to find applicable provisions. This makes *NFPA 5000* significantly more difficult to use and enforce. In addition, provisions will need to be added to *NFPA 5000* to address frost protection, footings on or adjacent to slopes, footing widths for light frame construction, design for expansive soil, pier foundations, and permissible bearing values for gravel and rock sites.

2001 CBC - Chapter 18A	IBC – Chapter 18	Comments
------------------------	------------------	----------

Division I - General	1801 - General	Similar
1801A – Scope		
References App. Chapter 33A, UBC Std. 18-1 (soils classification), UBC Std. 18-2 (expansion index test)		
1802A - Quality and Design	1801.2 Design	Similar
Refers to App. Ch. 33		
1803A - Soil Classification - Expansive Soil	1802.2.2 Expansive Soils	Similar; note that UBC Standards 18-1 and 18-2 discontinued
1804A - Foundation Investigation	1802 – Foundation and Soils Investigations	Similar, continue OSHPD amendments; evaluate SDC "C" provisions for non-adoption
A.1 General. OSHPD amends re:	2.1 General	
required geotechnical investigation	2.2 Where required (exception	
A.2 Investigation. OSHPD amends re: minimum # of borings,	clause)	
liquefaction analysis	2.2.1 Questionable soil	
A.3 Reports. OSHPD amends re:	2.2.2 Expansive soils	
liquefaction, high sulfate soils	2.2.3 Ground-water table	
A.4 Expansive Soils.	2.2.4 Pile and pier foundation	
A.5 Liquefaction Potential.	2.2.5 Rock strata 2.2.6 SDC C	
A.6 Adjacent Loads.	2.2.7 SDC D, E, F	
A.7 Drainage.	, ,	
	2.3 Soil classification	
	2.4 Investigation	
	2.5 Soil boring and sampling	
	2.6 Reports 1803.3 Site grading (addresses	
	A.7 provision pertaining to drainage around buildings)	
3301 – Excavations and Fills	1803 – Excavation, Grading and Fill	Similar; continue OSHPD amendments to 3301
<ul><li>1.1 General</li><li>1.2 Protection of adjoining</li></ul>	3.1 Excavations near footings or foundations	
property (see IBC 3307 for	3.2 Placement of backfill	
correlated provisions)	3.3 Site grading	
1.3 Protection of existing buildings	3.4 Grading and fill in floodways	
(OSHPD amendment, continue in	3.5 Compacted fill material	
2004 CBC)	3.6 Controlled low-strength material (CLSM)	
1805A - Allowable Foundation and Lateral Pressures	1804 – Allowable Load-Bearing Values of Soils	Similar (no OSHPD amendments to this CBC section)
Requires report based on bldg.	4.1 Design	
Size, type of const. and loads	4.2 Presumptive load-bearing values	
	4.3 Lateral sliding resistance	
	Table 1804.2 Allowable Foundation and Lateral Pressure	

OSHPD 7-14-03rev. 1 of 7

2001 CBC - Chapter 18A	IBC - Chapter 18	Comments
1806A - Footings A.1 General. OSHPD amends re: unformed footing size	1805 – Footings and Foundations 5.1 General 1805.4.2.6 Forming of concrete	Similar, continue OSHPD amendments (amend 1805.4.2.6)
A.2 Footing Design. OSHPD amends re: elastic analysis.  Model code provision refers to Div. III for slab/mat structure on expansive soils	5.4 Footings 1805.8 Design for expansive soils 1805.8.1 Foundations 1805.8.2 Slab-on-grade foundations 1805.8.3 Removal of expansive soil 1805.8.4 Stabilization	Similar, continue OSHPD amendment Evaluate 1805.8 for adoption/amendment
A.3 Bearing Walls. OSHPD amends to require shear wall footing to meet bearing wall footing requirements.	<ul><li>5.2 Depth of footings</li><li>5.4 Footings</li></ul>	Similar, continue OSHPD amendment
A.4 Stepped Foundations. OSHPD amends to limit step dimensions, detailing.	5.1 General	Continue OSHPD amendment
<ul> <li>A.5 Footings on or Adjacent to Slopes.</li> <li>1. scope</li> <li>2. clearance from ascending slope</li> <li>3. setback from descending slope</li> <li>4. pools (setback from pool wall)</li> <li>5. foundation elevation (drainage)</li> <li>6. alternate setback and clearance</li> </ul>	<ul> <li>5.3 Footings on or adjacent to slopes</li> <li>1. Building clearance from ascending slopes</li> <li>2. Footing setback from descending slope surface</li> <li>3. Pools</li> <li>4. Foundation elevation</li> <li>5. Alternate setback and clearance</li> </ul>	Similar
A.6 Foundation Plates or Sills.  1. DSA amend.  2. sills at bearing and shear walls, OSHPD amends to ref. 2320A.6  3. Additional requirements for Seismic Zones 3 and 4 - 2x2x 3/16 plate washers	1805.6 Foundation plate or sill bolting (refers to Chapter 23, does not contain any other provisions)	CBC provision not continued in IBC Chapter 18, refer to 2308.6 Continue OSHPD amendment in 2308.6
A.7 Seismic Zone 3 and 4. Requires #4 cont. top and bottom at foundation.	1805.9 Seismic requirements Refers to Sec. 1910	IBC provisions differ from CBC due to SDC; also see Chapter 19 Evaluate for amendment; repeal exception 1. and 2.
A.8 Designs Employing Lateral Bearing.  1. general (OSHPD amends re: pile and caisson elastic deformation)  2. design criteria; non-constrained and constrained  3. backfill  4. limitations	1805.7 Designs employing lateral bearing 1. Limitation 2. Design criteria; non-constrained and constrained 3. Backfill 1812 - Pier Foundations (see below)	Similar IBC provisions contained in 1812 are new (see below)

OSHPD 7-14-03rev. 2 of 7

2001 CBC - Chapter 18A	IBC – Chapter 18	Comments
A.9 Gillage Footings.	1805.4.4 Steel grillage footings	Similar
A.10 Bleacher Footings	-	No provisions found; evaluate for amendment
A.11 Pipes and Trenches (OSHPD amendment re: trench setback, sleeved pipes)	-	Continue OSHPD amendment
-	1805.4.2.3 Plain concrete footings	Do not adopt
-	1805.4.2.4 Placement of concrete	Adopt
-	1805.4.2.5 Protection of concrete	Adopt
-	1805.4.3 Masonry-unit footings	Evaluate
-	1805.4.5 Timber footings	Do not adopt
-	1805.4.6 Wood foundations	Do not adopt
-	1805.5 Foundation walls includes sections 1805.5.1 through 1805.5.7 and Tables 1805.5 (1) through (4)	Do not adopt (these provisions are new to code and provide for non-engineered basement walls)
1611A.6 Retaining Walls	1806 - Retaining Walls	Continue amendments of 1611A.6 in 1806
-	1807 Dampproofing and Waterproofing	New provisions to model code – evaluate for adoption
1807A - Piles - General Requirements	1808 – Pier and Pile Foundations	IBC provisions more extension, updated
A.1 General.	<ol> <li>Definitions</li> <li>Piers and Piles – General Requirements</li> <li>Design</li> <li>General</li> <li>Special types of piles</li> </ol>	IBC provisions more extensive, definitions new to model code
A.2 Interconnection	2.4 Pile caps	Similar
A.3 Determination of Allowable Loads A.4 Static Load Tests.	2.8 Allowable pier or pile loads - driving criteria - load tests - load test evaluation - allowable frictional resistance - uplift capacity - load bearing capacity - bent piers or piles - overloads on piers or piles	IBC provisions more extensive, updated
A.5 Column Action.	2.9 Lateral support	Similar
A.6 Group Action.	1808.2.2; item 9.	Similar
A.7 Piles in Subsiding Areas.	2.11 Piles in subsiding areas	Similar
A.8 Jetting.	2.13 Pre-excavation	Similar
A.9 Protection of Pile Materials.	2.17 Protection of pile materials	Similar
A.10 Allowable Loads.	2.8 Allowable pier or pile loads	Similar

OSHPD 7-14-03rev. 3 of 7

2001 CBC - Chapter 18A	IBC – Chapter 18	Comments
	also see 1808.2.8.4 (allowable frictional resistance)	
A.11 Use of Higher Allowable Pile Stresses.	2.10 Use of higher allowable pier or pile stresses	Similar
<u>-</u>	1808.2: 2.5 Stability 2.6 Structural integrity 2.7 Splices 2.12 Settlement analysis 2.14 Installation sequence 2.15 Use of vibratory drivers 2.16 Pile drivability 2.18 Use of existing piers or piles 2.19 Heaved piles 2.20 Identification 2.21 Pier or pile location plan 2.22 Special inspection 2.23 Seismic design of piers or piles (based on SDC, whether C, or D, E, F)	IBC contains new provisions, evaluate and adopt
1808A - Specific Pile Requirements	1809 - Driven Pile Foundations	IBC provisions more extension, updated
A.1 Round Wood Piles. 1.1 Material 1.2 Allowable stresses	1809.1 Timber piles 1.1 Materials 1.2 Preservative treatment 1.3 End-supported piles	Similar, IBC provisions updated, reference AF & PA NDS for design, ASTM D 25 and DOC PS-20 for material, and AWPA C3 for treatment
A.2 Uncased C-I-P Concrete Piles 2.1 Material 2.2 Allowable stresses	1810 - Cast-in-Place Concrete Pile Foundations  1810.1 General  1. Materials  2. Reinforcement (SDC-based provisions included)  3. Concrete placement  1810.2 Enlarged base piles  1. Materials  2. Allowable stresses  3. Installation  4. Load-bearing capacity  5. Concrete cover  1810.3 Drilled or augered uncased piles  1. Allowable stresses  2. Dimensions  3. Installation  4. Reinforcement  5. Reinforcement in SDC C, D, E or F	IBC provisions more extensive

OSHPD 7-14-03rev. 4 of 7

2001 CBC - Chapter 18A	IBC – Chapter 18	Comments
A.3 Metal-cased Concrete Piles (both CIP and driven) 3.1 Material 3.2 Installation 3.3 Allowable stresses	1810.4 Driven uncased piles 1. Allowable stresses 2. Dimensions 3. Installation 4. Concrete cover 1810.5 Steel-cased piles	Similar
	<ol> <li>Materials</li> <li>Allowable stresses</li> <li>Installation</li> <li>Reinforcement</li> <li>Construction</li> <li>Materials</li> <li>Design</li> <li>Structural core</li> <li>Allowable stresses</li> <li>Installation</li> </ol>	
<ul><li>A.4 Pre-cast Concrete Piles</li><li>4.1 Materials</li><li>4.2 Reinforcement ties</li><li>4.3 Allowable stresses</li></ul>	1809.2 Precast concrete piles 1. General 1.1 Design and manufacture 1.2 Minimum dimension 1.3 Reinforcement 2. Precast nonprestressed piles 2.1 Materials 2.2 Minimum reinforcement (SDC-based) 2.3 Allowable stresses 2.4 Installation 2.5 Concrete cover	IBC provisions more comprehensive, updated
A.5 Precast Prestressed Concrete Piles (Pretensioned) 5.1 Materials 5.2 Reinforcement 5.3 Allowable stresses	1809.2.3 Precast prestressed piles 1. Materials 2. Design (SDC-based) 3. Allowable stresses 4. Installation 5. Cover	IBC provisions more comprehensive, updated
A.6 Structural Steel Piles 6.1 Material 6.2 Allowable stresses 6.3 Minimum dimensions	<ol> <li>1809.3 Structural steel piles</li> <li>Materials</li> <li>Allowable stresses</li> <li>Dimensions of H-piles</li> <li>Dimensions of steel pipe piles</li> </ol>	Similar
A.7 Concrete-filled Steel Pipe Piles 7.1 Material 7.2 Allowable stresses 7.3 Minimum dimensions	1810.6 Concrete-filled steel pipe and tube piles 6.1 Materials 6.2 Allowable stresses 6.3 Minimum dimensions	Similar; IBC provisions updated

OSHPD 7-14-03rev. 5 of 7

2001 CBC - Chapter 18A	IBC – Chapter 18	Comments
	6.4 Reinforcement	
	6.5 Placing concrete	
-	1811 - Composite Piles	New provisions - evaluate for adoption
	1. General	
	2. Design	
	3. Limitation of load	
	4. Splices	
	5. Seismic reinforcement	
1806A.8 provisions are related	1812 - Pier Foundations	IBC 1812 provisions are new (primarily prescriptive
(see above)	1. General	construction requirements); evaluate for adoption and amendment
	Lateral dimensions and height	
	3. Materials	
	4. Reinforcement	
	<ul><li>5. Concrete placement</li><li>6. Belled bottoms</li></ul>	
	7. Masonry	
	8. Concrete	
	9. Steel shell	
	10. Dewatering	
1809A - Foundation	1805.4.2.2 Footing seismic ties	IBC incorporates SDC-based seismic design provisions
Construction - Seismic Zones 3	1805.5.5 Seismic requirements	within each section
and 4	(prescriptive foundation walls)	
A.1 General.	1805.9 Seismic requirements	
	(foundations for SDC D, E, F)	
A.2 Soil Capacity.	1802.2.7 Seismic design category D, E, or F. (soils investigation)	Similar
A.3 Superstructure-to-Foundation Connection.	1805.9 references ACI 318-02, Section 21.8	Similar
A.4 Foundation-Soil Interface.	1801.2.1 Foundation design for seismic overturning	Similar
A.5 Special Requirements for Piles and Caissons - OSHPD	1808.2.23 Seismic design of piers or piles	IBC contains more extensive requirements; evaluate for discontinuation of OSHPD amendments in CBC
amends for Sd, Se, Sf soils	1809.2.2.2 Minimum reinforcement (pre-cast driven piles; SDC-based requirements)	
	1809.2.3 Pre-cast prestressed piles; see 1809.2.3.2.1 (SDC C),	
	1809.2.3.2.2 (SDC D, E, F)	
	1810.1.2 Reinforcement (CIP	
	concrete pile); see 1810.1.2.1 for SDC C, 1810.1.2.2 for SDC D, E, F	
	1810.3.5 Reinforcement in SDC C, D, E, F (drilled or augered uncased piles)	
	1810.5.4.1 Seismic reinforcement (steel-cased piles)	
	1810.6.4.1 Seismic reinforcement	

OSHPD 7-14-03rev. 6 of 7

2001 CBC - Chapter 18A	IBC - Chapter 18	Comments
	(concrete-filled steel pipe and tube piles)	
	1811.5 Seismic reinforcement (composite piles)	
A.6 Inspection of Piles (OSHPD amendment)	1808.2.22 Special Inspection	Continue OSHPD amendment
A.7 Inspection of Caissons (OSHPD amendment)	1808.2.22 Special Inspection	Continue OSHPD amendment
Table 18A-I-A	Table 1804.2	Similar
Allowable Foundation and Lateral Pressure	Allowable Foundation and Lateral Pressure	
Table18A-I-B	-	No effect to OSHPD program
Classification of Expansive Soil		
Table 18A-I-C	Table 1805.4.2	Similar
Foundations for Stud Bearing Walls - Minimum Requirements	Footings Supporting Walls of light- Frame Construction	
Figure 18A-I-1	Figure 1805.3.1	Similar
Setback Dimensions	Foundation Clearances from Slopes	
-	Table 1805.5(1)	Do not adopt prescriptive design provisions
	Plain Masonry and Plain Concrete Foundation Walls	
-	Table 1805.5(2)	Do not adopt prescriptive design provisions
	8-Inch Concrete and Masonry Foundation Walls with Reinforcing Where d > 5 inches	
-	Table 1805.5(3)	Do not adopt prescriptive design provisions
	10-Inch Concrete and Masonry Foundation Walls with Reinforcing Where d > 6.75 Inches	
-	Table 1805.5(4)	Do not adopt prescriptive design provisions
	12-Inch Concrete and Masonry Foundation Walls with Reinforcing Where d > 8.75 Inches	

OSHPD 7-14-03rev. 7 of 7

2001 CBC - Chapter 18A	NFPA5000 - Chapter 36	Comments
Division I - General  1801A – Scope  References App. Chapter 33A, UBC Std. 18-1 (soils classification), UBC Std. 18-2 (expansion index test)	[Note - Chapter 36 is titled "Soils, Foundations, and Retaining Walls"] <b>36.1 Scope</b>	Similar
1802A - Quality and Design Refers to App. Ch. 33	-	No effect noted
3301 - Excavations and Fills 1.1 General 1.2 Protection of adjoining property 1.3 Protection of existing buildings (OSHPD amendment, continue in 2004 CBC)	36.2 Excavations  1. Scope 2. Protection of Excavations 3. Permanent Excavations 4. Fill 5. Site preparation	Similar scope; continue OSHPD amendments Evaluate 36.2.3.3 regarding phrase "safe side slopes, as determined by the AHJ", may need to repeal or establish specific requirements (consult CDMG) Review 36.2.4.3.2 for non-adoption (note also does not prescribe a standard for compaction) Evaluate
1803A - Soil Classification - Expansive Soil	36.3.3 Expansive Soils	Similar
1804A - Foundation Investigation  A.1 General. OSHPD amends re: required geotechnical investigation  A.2 Investigation. OSHPD amends re: minimum # of borings, liquefaction analysis  A.3 Reports. OSHPD amends re: liquefaction, high sulfate soils  A.4 Expansive Soils.  A.5 Liquefaction Potential.  A.6 Adjacent Loads.  A.7 Drainage.	36.3 Investigation and Bearing Capacity of Soil 1. Classification 2. Soil investigation 3. Expansive soils 4. Presumptive capacities  Site drainage - see 36.8.5 Site Grading	Continue OSHPD amendments  36.3.2.1 and 36.3.2.2 require evaluation prior to adoption No provisions to assess seismic effects (loading on retaining or basement walls, liquefaction, differential settlement, etc.)  For SDC C, D, E, F, ASCE 7-02 Sec. 9.7.4.1 requires investigation to address slope instability, liquefaction, spreading and surface rupture.
1805A - Allowable Foundation and Lateral Pressures Requires report based on bldg. Size, type of const. and loads	36.3.4 Presumptive Capacities Refers to Table 36.3.4(a) (allowable vertical load) and Table 36.3.4(b) (allowable lateral load)	Table 36.3.4(a) and (b) terms for "Class of Material"  Terms "soft", "medium", "hard", "compact", "loose" may be problematic for interpretation and use by typical users (non-geotechnical engineer) of these tables - evaluate and consult with CDMG to determine whether or not OSHPD can adopt, and if amendment is needed Evaluate footnote (a) of Table 36.3.4(a) regarding "unusual soil or moisture conditions" to determine if amendment or interpretation is needed
1806A - Footings A.1 General. OSHPD amends re: unformed footing size	36.4 Soil-Bearing Footings 36.4.1 General Provisions 36.4.1.2. (excavations)	Continue OSHPD amendment in 36.4.1.2, amend 36.4.1.2.2 to indicate 12" minimum
A.2 Footing Design. OSHPD amends re: elastic analysis.  Model code provision refers to Div. III for slab/mat structure on expansive soils	36.4.1.4 (slab, raft, mat foundations on expansive soils)	Continue OSHPD amendment in 36.4.1.1
A.3 Bearing Walls. OSHPD amends to require shear wall footing to meet bearing wall footing	-	Continue model code provision and amendment

OSHPD 7-13-03rev. 1 of 5

2001 CBC - Chapter 18A	NFPA5000 - Chapter 36	Comments
requirements.		
A.4 Stepped Foundations.	36.4.1.3	NFPA does not allow 10% slope at bottom. Continue
OSHPD amends to limit step dimensions, detailing.	30.4.1.3	OSHPD amendment provisions
A.5 Footings on or Adjacent to Slopes.	-	Develop amendments to continue CBC (model code) provisions
1. scope		
2. clearance from ascending slope		
3. setback from descending slope		
4. pools (setback from pool wall)		
5. foundation elevation (drainage)		
6. alternate setback and clearance		
<ul><li>A.6 Foundation Plates or Sills.</li><li>1. DSA amend.</li></ul>	36.6.3 Foundation Plate or sill bolting (makes general reference	NFPA 5000 nor referenced standard (NDS) prescribe any minimum sill bolting requirements. Only addressed
2. sills at bearing and shear walls, OSHPD amends to ref. 2320A.6	to Chapter 45; no specific provisions found in Chapter 45)	for 1 and 2 family dwellings if designed per AF&PA WFCM, but WFCM does not prescribe plate washer requirements.
3. Additional requirements for Seismic Zones 3 and 4 - 2x2x 3/16 plate washers		AF& PA Wind/Seismic Supplement prescribes minimum bolting for shear walls, and does prescribe plate washer requirements for designed shear walls.
		Develop amendments to maintain current provisions.
A.7 Seismic Zone 3 and 4.	-	Continue CBC provisions as amendment in 2004 CBC
Requires #4 cont. top and bottom at foundation.		
A.8 Designs Employing Lateral Bearing.	36.4.2 Design Using Lateral Bearing	Similar; continue OSHPD amendment in CBC item 1.
general (OSHPD amends re: pile and caisson elastic	36.4.3 Design Formula - No Constraint	
deformation)  2. design criteria; non-constrained and constrained	36.4.4 Design Formula - Constrained	
3. backfill		
4. limitations		
-	36.4.5 Flood Hazard Areas	Evaluate prior to adoption, consult DWR
A.9 Gillage Footings.	-	Evaluate to determine if amendment needed
A.10 Bleacher Footings	-	Evaluate to determine if amendment needed (also see Chapter 35 provisions regarding bleachers)
A.11 Pipes and Trenches (OSHPD amendment re: trench setback, sleeved pipes)	-	Continue OSHPD amendments
1807A - Piles - General	36.5 Pile Foundations	Amend 36.5.2 to prescribe geotechnical
Requirements	Conditions of use	investigation/report requirements per CBC
A.1 General.	2. Axial and lateral loads for piles	Evaluate 36.5.1.6 (interconnection of piles of min. 5% of pile load; CBC 1807A.2 is 10%, so min. design tie load is
A.2 Interconnection	3. Driven piles	1/2 of current requirement) Note: 36.1.1 specifies
A.3 Determination of Allowable Loads	4. Wood piles	conformance with ASCE 7-02, Sec. 9.7.4.3 of ASCE 7-
A.4 Static Load Tests.	5. Precast concrete piles	02 specifies 10% as minimum design load for SDC C or greater. NFPA 5000 Sec. 1.3.2 (precedence) states that
A.5 Column Action.	6. Prestressed precast concrete	NFPA 5000 Sec. 1.3.2 (precedence) states that NFPA 5000 provision would govern in case of conflict.
7 COMMIN ACTION.	piles	

OSHPD 7-13-03rev. 2 of 5

2001 CBC – Chapter 18A	NFPA5000 - Chapter 36	Comments
A.6 Group Action. A.7 Piles in Subsiding Areas. A.8 Jetting. A.9 Protection of Pile Materials. A.10 Allowable Loads. A.11 Use of Higher Allowable Pile Stresses.	7. Structural steel shapes 8. Cast-in-place concrete piles	Evaluate continuation of CBC 1807A Sec. A.7, A.9, A.11 as amendments to 2004 CBC  Evaluate 36.5.2.1 (dynamic load test) for adoption
1808A - Specific Pile Requirements  A.1 Round Wood Piles.  A.2 Uncased C-I-P Concrete Piles  A.3 Metal-cased Concrete Piles  A.4 Pre-cast Concrete Piles  A.5 Precast Prestressed Concrete Piles (Pretensioned)  A.6 Structural Steel Piles  A.7 Concrete-filled Steel Pipe Piles	36.5.3 Driven piles 36.5.4 Wood piles 36.5.5 Precast concrete piles 36.5.6 Prestressed precast concrete piles 36.5.7 Structural steel shapes 36.5.8 Cast-in-place concrete piles	Evaluate 36.5.3.1 - verify that plans and specifications are required per code to denote resistance/penetration requirements; should state "approved" plans CIP concrete pile provisions more comprehensive than CBC Structural steel pile requirements less than CBC - evaluate
	36.6 Foundation Walls  1. General requirements  - isolated piers  - isolated piers substituted for interior foundation walls  - flood hazard areas  2. Foundation wall thickness  - minimum thickness for concrete and masonry walls  - foundation walls not meeting parameters of Tables 36.6.2.2(a) through (d)  - thickness based on walls supported  - thickness based on soils loads, unbalanced backfill height, and wall height  - rubble stone  - foundation walls  - alternative concrete or masonry foundation wall reinforcement  36.6.3 Foundation Plate or sill bolting  36.6.4 Masonry pier and curtain wall foundations	Do not adopt prescriptive provisions for foundation walls (36.6.1, 36.6.2, 36.6.4) Amend 36.6.3 (see comments above)
-	36.7 Wood Foundation Systems	Do not adopt Sec. 36.7
-	36.8 Waterproofing and Dampproofing  1. Waterproofing required 2. Dampproofing required	New provisions to model code - evaluate for adoption (except 36.8.5, site grading, is similar to CBC provisions regarding site drainage

OSHPD 7-13-03rev. 3 of 5

2001 CBC - Chapter 18A	NFPA5000 - Chapter 36	Comments
	<ul><li>3. Foundation drain</li><li>4. Floor base</li><li>5. Site grading</li></ul>	
1611A.6 Retaining Walls	36.9 Retaining Walls  1. Design  2. Hydrostatic pressure  3. Concrete retaining walls  4. Reinforced masonry retaining walls  5. Segmental retaining walls (ref. NCMA Design Manual for Segmented Retaining walls	Continue amendments of 1611A.6 in 36.9 36.9.1 does not prescribe FOS for overturning, sliding, soil pressure, and uplift (amend to maintain current CBC requirements)
1809A - Foundation Construction - Seismic Zones 3 and 4  A.1 General. A.2 Soil Capacity. A.3 Superstructure-to-Foundation Connection. A.4 Foundation-Soil Interface. A.5 Special Requirements for Piles and Caissons - OSHPD amends for Sd, Se, Sf soils A.6 Inspection of Piles (OSHPD amendment) A.7 Inspection of Caissons (OSHPD amendment)	36.1.1 (refers to ASCE 7-02, Section 9 and A9.7 for SDC C, D, E, F locations)  36.6 (foundation wall) provisions reference ASCE 7 limitations (general reference)	Evaluate ASCE 7-02 provisions for any needed amendments Continue A.6, A.7 amendments
Table 18A-I-A Allowable Foundation and Lateral Pressure	Table 36.3.4(a) Maximum Allowable Soil Pressures  Table 36.3.4 (b) Maximum Allowable Lateral Soil Pressures	Table 36.3.4(a) and (b) terms for "Class of Material"  Terms "soft", "medium", "hard", "compact", "loose" may be problematic for interpretation and use by typical users (non-geotechnical engineer) of these tables - evaluate and consult with CDMG to determine whether or not OSHPD can adopt, and if amendment is needed Evaluate footnote (a) of Table 36.3.4(a) and (b) regarding "unusual soil or moisture conditions" to determine if amendment or interpretation is needed  Table 36.3.4(b) does not contain lateral sliding coefficients and resistance data
Table18A-I-B Classification of Expansive Soil	-	No effect to OSHPD program
<b>Table 18A-I-C</b> Foundations for Stud Bearing Walls - Minimum Requirements	-	Evaluate for amendment; prescriptive requirements used for light-frame structures
Figure 18A-I-1 Setback Dimensions	-	Develop amendments to continue CBC provisions
-	Table 36.6.2.2(a) Plain Masonry and Plain Concrete Foundation Walls	Do not adopt

OSHPD 7-13-03rev. 4 of 5

2001 CBC - Chapter 18A	NFPA5000 - Chapter 36	Comments
-	Table 36.6.2.2(b)	Do not adopt
	8-Inch Reinforced Concrete and Masonry Foundation Walls Where d is Greater Than or Equal to 5 Inches-Reinforced Masonry	
-	Table 36.6.2.2(c)	Do not adopt
	10-Inch Reinforced Concrete and Masonry Foundation Walls Where d is Greater Than or Equal to 6.75 Inches-Reinforced Masonry	
-	Table 36.6.2.2(d)	Do not adopt
	12-Inch Reinforced Concrete and Masonry Foundation Walls Where d is Greater Than or Equal to 8.75 Inches-Reinforced Masonry	

OSHPD 7-13-03rev. 5 of 5